

APPLICATION UNDER UNITED STATES PATENT LAWS

Atty. Dkt. No. PM 271598/T4YK-00S0603
(M#)

Invention: OPTICAL HEAD DEVICE AND DISK DRIVE SYSTEM

Inventor (s): UCHIYAMA, Mineharu

Pillsbury Madison & Sutro LLP
Intellectual Property Group
1100 New York Avenue, NW
Ninth Floor
Washington, DC 20005-3918
Attorneys
Telephone: (202) 861-3000

This is a:

- ☐ Provisional Application
- ☒ Regular Utility Application
- ☐ Continuing Application
- ☐ PCT National Phase Application
- ☐ Design Application
- ☐ Reissue Application
- ☐ Plant Application
- ☐ Substitute Specification
Sub. Spec. Filed _____
in App. No. _____ / _____
- ☐ Marked up Specification re
Sub. Spec. filed _____
In App. No _____ / _____

SPECIFICATION

09616364.07.1300

TITLE OF THE INVENTION

Ins. A15

~~OPTICAL HEAD DEVICE AND DISK DRIVE SYSTEM~~

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the benefit of priority from the prior Japanese Patent Applications No. 11-199464, filed July 13, 1999; and No. 2000-206937, filed July 7, 2000, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

10 This invention relates to an optical head device effective in reading or recording the signal from or onto various types of optical recording mediums (including a digital video disk (DVD) and a compact disk (CD)).

15 In the field of recording mediums, DVD has recently been developed which enables high-density recording, although having the same diameter (12 cm) as that of a conventional CD on which audio or digital data is recorded. Since having the high recording density, DVD requires a beam of light of a shorter wavelength (650 nm) than the wavelength (780 nm) of
20 a beam of light used to read the data on the CD.

It is desirable that a reproducing apparatus should be capable of playing back a disk system of
25 both the CD type and the DVD type. Thus, a disk system with a CD light source (with a wavelength of 780 nm) and a DVD light source (with a wavelength of 650 nm)

09616364-071300

has been developed as an optical head device (or an optical pickup) using a multi-wavelength semiconductor array.

5 The optical head device includes a first
light source and a second light source and further
a diffraction grating to which the light from either
of the first or second light source is directed.
The diffraction grating particularly separates a CD
light beam into three beams. The beams of light
10 emitted from the diffraction grating pass through
a hologram and then through a collimator lens and
turn into collimated light. The collimated light
enters an objective lens. The light gathered by the
objective lens is projected onto the recording surface
15 of a disk. The light reflected from the disk passes
through the objective lens and the collimator lens
and enters the hologram. The hologram diffracts the
reflected light and directs it to a photodetector
composed of photodiodes. The photodetector outputs
20 a focus error signal, a tracking error signal, and
a read signal.

25 (A1) In the optical head device, when the device
is set in the CD reading state, the laser beam with a
wavelength of 780 nm from the light source is inputted
to the diffraction grating, which then outputs three
beams. One of the three beams is the main beam and the
remaining two are sub-beams. The intensity ratio of

09616364, 071300

the main beam to the sub-beam is about 8:1.

When the device is set in the DVD reading state, the laser beam with a wavelength of 650 nm from the light source also passes through the diffraction grating. This permits unnecessary side beams to occur. As a result, the efficiency of the main beam decreases. Naturally, in the photodetector receiving the reflected light from the disk, the light-receiving efficiency of the main beam decreases. This causes the problem of degrading the C/N of the signal. To improve the C/N of the signal, the amount of emission of a DVD light source may be increased. With this approach, however, there is a strong possibility that the device will be used beyond the maximum rating of the semiconductor laser, impairing the reliability of the device.

(B1) A conventional equivalent has disadvantages in that its overall mechanism is complex and its structure is great.

(C1) In the optical head device that reads both of CD and DVD signals, birefringence components might take place in the reflected light from a CD. In that case, the amount of light received by the photodetector fluctuates. The large amount of birefringence components causes a problem: the playback signal deteriorates seriously.

(D1) In the optical head device, when a first light source for DVD and a second light source for CD

09016364.071300

are used, the quality of the playback signal tends to deteriorate.

(E1) In addition, there is another problem: the level of the focus error signal in DVD playback drops.

5 (F1) There is still another problem: the quality of the focus error signal deteriorates.

(G1) To play back either a CD or DVD, a good playback performance is needed. To satisfy this requirement, a method of aligning the position of each component part must be improved.

10

BRIEF SUMMARY OF THE INVENTION

(A2) Regarding the problem in (A1), an object of the present invention is to provide an optical head device which produces side beams when using a light source of a second wavelength but does not produce any side beam when using a light source of a first wavelength, thereby increasing the light use efficiency of the first light source.

15

(B2) Regarding the problem in (B1), an object of the present invention is to provide an optical head device capable of producing a side beam unique to each laser beam without increasing the overall structure of the device, even when using a laser light-emitting element having light sources in very close positions in such a manner that they correspond to disks.

20

25

(C2) Regarding the problem in (C1), an object of the present invention is to provide an optical head

00616364-071300

device which has an optical layout providing a good playback performance for both DVD and CD.

5 (D2) Regarding the problem in (D1), an object of the present invention is to provide an optical head device which has not only a small difference between the best tilt angles of the respective beams for DVD and CD in the optical head using a semiconductor laser array but also a good playback performance.

10 (E2) Regarding the problem in (E1), an object of the present invention is to provide an optical head device which generates a good-quality focus error signal in playing back both of DVD and CD.

15 (F2) Regarding the problem in (F1), an object of the present invention is to provide an optical head device which has the optimum distance between the semiconductor laser array and the hologram.

20 (G2) Furthermore, an object of the present invention is to provide a method of installing a hologram in an optical head device in such a manner that the accuracy of installing a semiconductor laser is alleviated and, even in the alleviated state, the effect of impairing the playback performance is reduced.

25 (A3) The object in item (A2) is accomplished by providing an optical head device comprising a first light source for emitting a light beam of a first wavelength, a second light source which is placed at

09616364-071300

almost the same position as that of the first light source and emits a light beam of a second wavelength differing from the first wavelength, and a diffraction grating which has a first-order diffraction efficiency of almost zero for the light beam from the first light source and emits the first-order diffraction light for the light beam from the second light source. With this configuration, the light use efficiency of the second light source is increased.

(B3) The object in item (B2) is accomplished by providing an optical head device comprising light-emitting means for emitting laser beams from adjacent positions, a light-receiving element for receiving the reflected light from an optical disk, a hologram for diffracting the reflected light from the optical disk toward the light-receiving element, and a diffraction grating which is placed between the hologram and the light-emitting means in such a manner that the laser beams strike at separate positions and which diffracts the laser beam emitted from at least one of the light sources. With this configuration, an optical integrated element applicable to more than one disk system is obtained without making the overall structure of the optical system larger.

(C3) To achieve the object in item (C2), a nonpolarization blaze hologram is used as an element for directing the reflected light to the photodetector.

09515354.071300

With this approach, the light use efficiency is
1.5 time as high as that of a usual hologram, when
a nonpolarization rectangular hologram is used,
which improves the DVD playback performance. Use of
5 a nonpolarization hologram prevents the amount of light
received from fluctuating due to birefringence, which
provides a stable playback signal.

(D3) To achieve the object in item (D2),
the optical axis of the second light source for CD
10 is aligned close with the optical axis of the
objective. This permits oblique incidence to occur
on the objective lens in DVD, but prevents oblique
incidence from occurring in CD. Since in a DVD/CD
interchangeable objective lens, the aberration
15 caused by oblique incidence in DVD is astigmatism,
the deterioration of the best tilt angle and
the performance of the playback signal becomes less,
which makes the difference between the best tilt
angle in DVD and that in CD small and provides a good
20 playback performance of playback signal.

(E3) To accomplish the object in item (E2),
the center of the hologram is placed at the midpoint
between the optical axis of the first light source and
that of the second light source. This makes both the
25 amplitude of the focus error signal in CD playback and
that in DVD playback suitable, which improves the
quality of the focus error signal in the entire device.

09615354.071300

5

10

20

25

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the invention.

and together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the principles of the invention.

5 FIG. 1 shows the configuration of an optical head device according to an embodiment of the present invention;

 FIG. 2A shows the configuration of the photodetector in FIG. 1;

10 FIG. 2B is a diagram to help explain beam spots in reading the recorded data on a disk by a three beam method;

 FIG. 3A is a characteristic diagram of phase grating depth and diffraction efficiency to help
15 explain the principle of the present invention;

 FIG. 3B shows the depth of the grating to help explain the principle of the present invention;

 FIGS. 4A and 4B are diagrams to help explain a diffraction grating according to another embodiment
20 of the present invention;

 FIG. 5A shows the recording surface of a CD, FIG. 5B shows the recording surface of a DVD-ROM, and FIG. 5C shows the recording surface of a DVD-RAM;

 FIG. 6 shows an example of the electric signal processing route in an optical head device according to
25 the present invention;

 FIG. 7A is an explanatory diagram of a device

00616364.071300

using an nonpolarization hologram, showing another embodiment of the present invention;

FIGS. 7B and 7C show examples of an nonpolarization hologram used in the device of FIG. 7A;

5 FIG. 7D is an explanatory diagram showing fluctuations in a playback signal;

FIG. 8A is an explanatory diagram of a device where the optical axis of the objective lens placed asymmetrically with the optical axis of the first light source and that of the second light source, showing still another embodiment of the present invention;

10

FIG. 8B shows the relationship between oblique incidence and the best tilt angle;

FIG. 8C shows the relationship between oblique incidence and jitters in the playback signal;

15

FIG. 9A shows still another embodiment of the present invention;

FIGS. 9B and 9C are explanatory diagrams of beam spots projected on the hologram;

FIG. 10A is an explanatory diagram of a device where the center of the hologram is shifted from the optical axis of the objective, showing still another embodiment of the present invention;

20

FIG. 10B shows the relationship between the photodetector and the beam spots of the reflected light;

25

FIG. 11A is a side view of the device of FIG 10A;

09515354.071300

FIG. 13B shows an example of a marker attached to the hologram;

FIG. 13C is a diagram to help explain the work of aligning the positions of component parts;

5 FIGS. 13D and 13E show examples of beam spots projected on the photodetector;

FIG. 14A is a diagram to help explain the work of aligning the positions of component parts in another method of assembling a device related to the present invention; and
10

FIGS. 14B and 14C show examples of beam spots projected on the photodetector.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, referring to the accompanying drawings, embodiments of the present invention will be explained.
15

FIG. 1 shows an embodiment of the present invention. A semiconductor laser device 11, which is what is called a chip laser (a single block), has a CD light source 1b (for outputting a beam of light with a wavelength of 780 nm) and a DVD light source 1a (for outputting a beam of light with a wavelength of 650 nm) in such a manner that they are close to each other. The light emitted from the so-called multi-wavelength semiconductor laser device 11 passes through a diffraction grating 12 and a hologram 13 and enters a collimator lens 14. The light emitted from
20
25

00616364.071300

the collimator lens 14 turns into collimated light, parallel light, and enters an objective lens 15. The light going from the light source to a recording medium is referred to as transmit light. The light
5 converged at the objective lens 15 is projected onto pit trains (information recording tracks) in a recording medium.

The light reflected from the recording medium passes through the objective lens 15 and collimator
10 lens 14 and enters the hologram 13. The hologram 13 refracts the reflected light and directs it to a photodetector 16.

The photodetector 16 is composed of, for example, quadrisected photodiodes 6A, 6B, 6C, and 6D for main
15 beam (a single beam) and photodiodes 6E and 6F for side (sub) beams provided on both sides of the photodiodes 6A, 6B, 6C, and 6D as shown in FIG. 2A.

FIG. 2B shows the relationship between pit trains (tracks) in a CD and three beams. Ideally, the main
20 beam follows the center line of a read pit train (track) and the front and back sub-beams track the right and left ends of the pit train. Therefore, when the difference between the photoelectric conversion outputs from the photodiodes 6E and 6F of
25 the photodetector 16 is obtained, the difference component can be used as a tracking error signal.

The present invention is characterized by having

09515364.071300

the following characteristic of the diffraction grating 12 described below.

FIG. 3A shows a characteristic of the depth of the phase grating of the diffraction grating 12, the 0-order diffraction efficiency, and the first-order diffraction efficiency. The ordinate axis indicates diffraction efficiency and the abscissa axis indicates the depth of phase grating. In a conventional diffraction grating, the depth of phase grating to the wavelength of the second light source for CD is about $(1/3)\pi$ (a in FIG. 3B). In such a case, because the first-order diffraction efficiency also has an effect on the light beam from the first light source for DVD, unnecessary side beams appear.

The diffraction grating 12 of the present invention, however, is designed to satisfy the following equation:

$$h_0 = \lambda_1 / (n - 1)$$

where λ_1 is the wavelength of the first light source for DVD, n is the refractive index, and h_0 is the depth of the grating groove.

The phase grating depth ϕ_0 of the diffraction grating is calculated using the following equation:

$$\phi_0 = 2\pi \cdot h_0 \cdot (n - 1) / \lambda$$

The relationship between the phase grating depth ϕ_0 and the diffraction efficiency η is as shown in FIG. 3A. Since the wavelength of the light beam from

00616364-071300

the first light source for DVD is λ_1 , the following equations are fulfilled:

$$\phi_0 = 2\pi \cdot h_0 \cdot (n - 1) / \lambda_1 = 2\pi$$

It follows that the 0-order diffraction efficiency
5 $\eta_0 = 100\%$ and the first-order diffraction efficiency
 $\eta_1 = 0\%$. When the first-order diffraction efficiency
is 0, this means that no sub-beam (diffraction light)
occurs. The groove of the phase grating of the
diffraction grating 12 that realizes no sub-beam is
10 about five times as deep as that shown by a in FIG. 3B.

With the present invention, when the light source
requiring no sub-beam (the DVD light source) is used in
the optical path of the optical pickup, a diffraction
grating whose grating groove has a depth of $m/(n - 1)$
15 of the wavelength of the light source (where m is
a natural number and n is the refractive index of
the diffraction grating) is used. This prevents side
beams from occurring in the DVD mode, increasing the
main-beam receiving efficiency, which contributes to
20 an improvement in the C/N of the signal without raising
the amount of emission of the light source.

When the second light source (CD light source) is
used, it goes as follows. The diffused light emitted
from the light source 1b enters the diffraction
25 grating 12. Since the wavelength of the second light
source is λ_2 , the phase grating depth ϕ_0 of the
diffraction grating 12 is:

09616364.07.1300

$$\phi_0 = 2\pi \cdot \lambda_1 / \lambda_2$$

Since $\lambda_2 = 780$ nm and $\lambda_1 = 650$ nm, this gives
 $\phi_0 = 1.67\pi$. At this time, from the characteristic of
FIG. 3A, it follows that the 0-order diffraction
5 efficiency η_0 = about 75% and the first-order
diffraction efficiency η_1 = about 10%. Then, the main
beam of order 0 and \pm first-order side beams occur.
This enables the diffraction grating 12 to sense the
tracking error signal by a so-called three-beam method.

10 As explained above, with the optical head device
of the present invention, when the light source 1b for
CD is used, side beams necessary to sense a tracking
error signal can be generated. When the light source
1a for DVD is used, side beams are prevented from
15 occurring, which suppresses the loss of the light
emitted from the light source 1a. This assures a
suitable relationship between the amount of emission
from the light source 1a and the quality of the
playback signal, which improves the quality and
20 reliability of the optical pickup device.

The present invention is not limited to the above
embodiment.

When the optical head device is used in a system
which senses a tracking error signal by a differential
25 push-pull method, as in a DVD-RAM, it may be
constructed as follows.

The grating groove depth h_0 of the diffraction

5

10

15

20

25

other diffraction grating is designed to realize a differential push-pull method of sensing a tracking error sense signal in DVD-RAM recording.

While in the above embodiment, the gratings are formed on one side of the diffraction grating 21, the diffraction grating characteristic on one side may differ from that on the other side as shown in FIG. 2B. For example, the side 22A may be so designed that, when the light source for DVD is used, the first-order diffraction efficiency is 0 and that, when the light source for CD is used, the first-order diffraction efficiency is 10% and the 0-order diffraction efficiency is 75%. Moreover, the other side 22B may be designed to realize a differential push-pull method of sensing a tracking error sense signal in DVD-RAM recording.

Since the relationship between the phase grating depth ϕ_0 and the diffraction efficiency η varies at periodic intervals of a phase of 2π , the diffraction efficiency of the side beam can be set at a desired value by setting the grating groove depth h_0 at m (m is a natural number) times $h_0 = \lambda_1/(n - 1)$ or $h_1 = \lambda_2/(n - 1)$.

The semiconductor laser device may be separate semiconductor lasers located close to each other, instead of the multi-wavelength semiconductor laser array.

Next, the pit structure of a disk from which the optical head device of the present invention reads the data will be explained.

FIG. 5A shows the structure of the recording surface of a CD, FIG. 5B shows the structure of the recording surface of a DVD-ROM, and FIG. 5C shows the structure of the recording surface of a DVD-RAM. An optical disk where the track pitch differs greatly from the shortest pit length requires a light source that provides light beams of the aforementioned different wavelengths.

FIG. 6 shows an example of the electric signal processing route for processing the signal read by the optical head device. The photodetector 16 includes the photodiodes 6A, 6B, 6C, 6D, 6E, and 6F as explained in FIG. 2A. The outputs of the photodiodes 6A, 6B, 6C, 6D, 6E, and 6F are supplied to buffer amplifiers 23a, 23b, 23c, 23d, 23e, and 23f, respectively. The signals A to F outputted from the buffer amplifiers 23a, 23b, 23c, 23d, 23e, and 23f are calculated as described below.

An adder 231 produces signal $(A+C)$ and an adder 232 produces signal $(B+D)$. Using signal $(A+C)$ from the adder 231 and signal $(B+D)$ from the adder 232, an adder 233 produces $(A+C) - (B+D)$. The signal $(A+C) - (B+D)$ is used as a focus error signal.

An adder 234 produces signal $(A+C)$ and an adder

00616364.071300

235 produces signal (B+D). The signals (A+C) and (B+D) are inputted to a phase difference sensor 31. The output of the phase difference sensor 31 is used as a DVD tracking error signal. When a switch 322 is
5 turned off, signal (E-F) obtained on the basis of the sub-beam sense signal is ignored.

The signals (A+B) and (C+D) are also inputted to an adder 236. The adder 236 produces signal (A+B+C+D) (hereinafter, referred to as signal HF).

10 Signal E and signal F are inputted to an adder 237. The adder 237 produces signal (E-F). The signal (E-F) is used as a CD tracking error signal. When the device is in the CD playback mode, the switch 322 is turned on. The above circuit configuration is
15 available in various embodiments of the invention and is not restricted to the above configuration.

The present invention is not limited to the above embodiment.

According to the present invention, there is
20 provided an optical head device with an optical layout assuring a good reproduction performance for a first disk (e.g., DVD) and a second disk (e.g., CD). The optical head device uses a nonpolarization blaze hologram as an element for directing the reflected
25 light to the photodetector. Because this configuration achieves about 1.5 times the light use efficiency of an ordinary hologram when a nonpolarization rectangular

09616364.071300

hologram is used, the DVD playback performance is improved. Use of a nonpolarization hologram prevents CD birefringence from varying the amount of light received, producing a stable playback signal.

5 As a bad example of an optical head device, it is assumed that a $(1/4)\lambda$ plate is provided between the hologram and the objective and the linearly polarized light (P polarized light) is turned into a circularly polarized light in the transmit light system and the
10 circularly polarized light is turned into a linearly polarized light (S polarized light) in the reflected light. This is because the S polarized light reflected from the optical disk is polarized into the first-order diffraction light at the hologram and the polarized
15 light is directed to the photodetector. The hologram has a high efficiency of the 0-order diffraction light with respect to P polarized light and a high efficiency of the first-order diffraction light with respect to S polarized light.

20 It is desirable that the hologram should have a high light use efficiency. When such a polarizing element system (including the $(1/4)\lambda$ plate and polarization hologram) is used, the amount of light received by the photodetector varies due to the
25 birefringence of the disk. This causes a problem: when the amount of birefringence of the disk is greater than the value in the specification, the playback

00616364.071300

signal fluctuates significantly. In the case of DVD, since its standard is severe, products with the amount of birefringence greater than that in the specification are not put on the market. In contrast, since CD

5 products with the amount of birefringence greater than that in the specification have been on the market, a pickup device using the polarizing element system undergoes fluctuations in the amount of light received and has a great effect on the playback performance.

10 When an optical pickup using a multi-wavelength semiconductor array is used as described above, a hologram is shared by DVD and a CD. Thus, use of a polarization hologram causes a problem: the playback signal fluctuates significantly due to the

15 birefringence at the CD surface.

To overcome this problem, a nonpolarization hologram 13 as shown in FIG. 7B or 7C in the configuration as shown in FIG. 7A is used. In FIG. 7A, the same parts as those in FIG. 1 are indicated by the

20 same reference symbols.

In the invention, a hologram whose grating is of a blaze shape is used. The grating of the hologram may be of an asymmetrical shape as shown in FIG. 7B or take the form of asymmetrical steps as shown in FIG. 7C.

25 In the semiconductor laser device 11, the first light source 1a outputs a DVD beam with a wavelength of 650 nm and the second light source 1b outputs a CD beam

09516364-071300

with a wavelength of 780 nm. The hologram 13 is a blaze hologram where the 0-order diffraction efficiency is almost the same as the + first-order diffraction efficiency and the - first-order diffraction efficiency is lower than the 0-order or first-order diffraction efficiency. The hologram 13 is a nonpolarization hologram, where the diffraction efficiency does not vary according to the direction of polarization of incident light (P or S polarized light).

In DVD playback, the light emitted from the first light source 1a enters the hologram 13. The 0-order light emitted from the hologram 13 is converted by the collimator lens 14 into collimated light, which then enters the objective lens 15. The objective lens 15 projects the collimated light in such a manner that the light converges on the recording surface of the optical recording medium. The reflected light from the optical recording medium passes through the objective lens 15 and collimator lens 14 and enters the hologram 13. The + first-order light emitted from the hologram 13 is directed to the photodetector 16. In the photodetector 16, the light is converted by the photoelectric conversion element into an electronic signal.

In CD playback, the second light source 1b is used. The light emitted from the light source 1b passes through the same route as described above and is

09616364, 07.1300

directed to the photodetector 16. In the photodetector 16, the reflected light from the optical disk is converted by the photoelectric conversion element into an electronic signal.

5 With the above configuration, the light use efficiency is improved, stepping up the DVD playback performance. Use of the nonpolarization hologram prevents the amount of light received from fluctuating greatly due to birefringence, providing a stable
10 playback signal. Although an optical system using the aforementioned polarizing element system (including a $(1/4)\lambda$ plate and a polarization hologram) permits the amount of light received to fluctuate due to the birefringence of a CD and therefore the playback signal
15 RS varies significantly as shown in FIG. 7D, the optical head device of the present invention does not have such a problem.

 The present invention is not limited to the above embodiments.

20 According to the present invention, there is provided an optical head device where the difference between the best tilt angle of DVD and that of CD is small and the playback signal performance is good in an optical head using a semiconductor laser array.
25 To achieve this, the optical axis of the second light source for CD is aligned close with the optical axis of the objective. With this arrangement,

09516364.071300

the DVD light beam enters the objective obliquely,
whereas the CD light beam does not enter the objective
obliquely. In a DVD/CD interchangeable objective, the
aberration caused by the oblique incidence of DVD is
5 astigmatism, thus decreasing the best tilt angle and
the deterioration of the playback signal performance,
which makes the difference between the best tilt angle
of DVD and that of CD smaller and provides a good
playback signal performance.

10 FIGS. 8A - 8C shows the embodiment of the
invention.

As shown in FIG. 8A, the optical axis of the
second light source 1b for CD is caused to almost
coincide with the optical axis of the objective
15 lens 15.

In DVD playback, the diffuse light emitted from
the first light source 1a enters the hologram 13.
The light emitted from the hologram 13 is converted
by the collimator lens 14 into collimated light,
20 which then enters the objective lens 15. The objective
lens 15 projects the collimated light in such a manner
that the light converges on the recording surface of
the optical recording medium. The reflected light
from the optical recording medium passes through the
25 objective lens 15 and collimator lens 14 and enters
the hologram 13. The + first-order light diffracted by
and emitted from the hologram 13 is directed to the

09616364-071300

photodetector 16. In the photodetector 16, the light is converted by the photoelectric conversion element into an electronic signal.

5 In CD playback, the second light source 1b is used. The light emitted from the light source 1b passes through the same route as described above and is directed to the photodetector 16. In the photodetector 16, the reflected light from the optical disk is converted by the photoelectric conversion element into
10 an electronic signal.

The objective lens 15 can be driven by a servo system in the focusing direction and the tracking direction in such a manner that an objective driving unit can cause the objective to follow the surface jolt
15 or the decentering of the disk.

FIG. 8B shows the relationship between an angle of the oblique incidence of the light beam striking the objective lens 15 and best tilt angle. FIG. 8C shows the relationship between the angle of the oblique
20 incidence of and jitters in the light beam striking the objective lens 15. The "best tilt angle" is the angle at which the disk is inclined to the base plane of the optical apparatus. While the disk is inclined at this angle, best possible signals can be reproduced from the
25 disk. The DVD/CD interchangeable objective lens 15 is designed to give priority to DVD. The priority to DVD means that parameters or factors, curvature and focal

09616364, 071300

distance, etc, on the design are selected to desirable to DVD playback. In DVD playback, the objective lens 15 causes astigmatism for oblique incidence. On the other hand, when the objective lens 15 is used in playing back a CD, it causes coma because oblique incidence collapses the sine condition. Thus, in CD playback, the best tilt angle and jitter characteristic deteriorate, but the degree of deterioration is low in DVD.

Taking into account the above characteristics, the first light source and second light source are placed asymmetrically with the optical axis of the objective lens 15 as shown in FIG. 8A. Then, the optical axis of the objective lens 15 is caused to coincide with the optical axis of the CD light source.

With this arrangement, when the light source 1b for CD is used, there is no oblique incidence on the objective lens 15, which helps prevent the best tilt angle and jitter characteristic from deteriorating.

When the DVD light source 1a is used, there is oblique incidence on the objective lens 15. However, because the aberration caused by oblique incidence dominate astigmatism, the deterioration of the best tilt angle and jitter characteristic lies in the permitted range.

As described above, the device of the invention comprises the first and second light sources and the objective lens 15. The first light source and second

light source are arranged asymmetrically with the optical axis of the objective lens 15.

If the thickness of the substrate of a first optical disk is t_1 , the thickness of the substrate of a second optical disk is t_2 , the distance between the axis of the first light source and the optical axis of the objective lens is δ_1 , and the distance between the axis of the second light source and the optical axis of the objective lens is δ_2 , it is desirable that the following expressions should be satisfied: $t_1 < t_2$ and $\delta_1 > \delta_2$. The optical axis of the second light source is caused to almost coincide with the optical axis of the objective. The first and second light sources constitute a multi-wavelength semiconductor laser device.

In the embodiment(s) described above, the objective lens 15 is one designed to be fit in reproducing data signals from DVDs. Nonetheless, the objective lens 15 may be designed for use in reproducing data signals from CDs. In this case, the characteristic curves of the (DVD) and the characteristic curve of the (CD) shown in FIGS. 8B and 8C are interchanged. Thus, it is desired that the optical axis of the objective lens 15 be aligned with the optical axis of the light source (1a) provided for the DVD.

In this case, the DVD/CD interchangeable objective

00315364.071300

5 In CD playback, the objective lens 15 causes
astigmatism for oblique incidence. On the other hand,
when the objective lens 15 is used in playing back a
DVD, it causes coma because oblique incidence collapses
the sine condition. Thus, in DVD playback, the best
0 tilt angle and jitter characteristic deteriorate, but
the degree of deterioration is low in CD.

15

20 When the CD light source (1b) is used, there is oblique incidence on the objective lens 15. However, because the aberration caused by oblique incidence dominate astigmatism, the deterioration of the best tilt angle and jitter characteristic lies in the permitted range.

Since the numeric aperture of CD is smaller than that of DVD, the aberration caused by oblique incidence in the DVD/CD interchangeable objective lens 15

designed priority to CD is less than that of the DVD/CD interchangeable designed priority to DVD. If the objective lens designed as priority to DVD, when the optical axis of the CD light source is inclined, the best tilt angle and jitter characteristic deteriorate. This is because of a generation of the aberration is in proportion to the cube of the numeric aperture.

In the above embodiment, if thickness of the substrate of a first optical disk is t_1 , the thickness of the substrate of a second optical disk is t_2 , the distance between the axis of the first light source and optical axis of the objective is δ_1 , and the distance between the axis of the second light source and the optical axis of the objective lens is δ_2 , it is desirable that the following expressions should be satisfied;

$$t_1 > t_2 \text{ and } \delta_1 < \delta_2$$

The present invention is not restricted to the above embodiment.

In the present invention, a good-quality focus error signal can be obtained in both of DVD playback and CD playback. Therefore, the invention is characterized in that the center of the hologram is placed halfway between the optical axis of the first light source and that of the second light source. This sets both the amplitude of the focus error signal in CD playback and that in DVD playback at a suitable

level, which improve the quality of the focus error signal for the entire device.

FIGS. 9A, 9B, 9C, 10A and 10B are diagrams to help explain the embodiment.

5 As shown in FIG. 9A, it is assumed that the center of the hologram 13 is on the optical axis of the second light source 1b and coincides with the optical axis f of the objective lens 15. In this situation, the area of the hologram through which the light beam passes is as follows. FIG. 9B shows a case where the second light source 1b (for CD) is used and the hologram pattern 3a is concentric with the playback beam 9a. In contrast, FIG. 9C shows a case where the first light source 1a (for DVD) is used, the hologram pattern 3a and playback beam 9b have shifted significantly in the direction in which the light sources are arranged.

10

15

Such a state causes the amplitude of the focus error signal to decrease significantly. To avoid this drawback, the optical axis 151 of the objective lens 15 is caused to align close with the optical axis of the second light source 1b. The center (= the origin of a phase transfer function) axis 131 of the hologram 13 is placed almost at the midpoint between the optical axis of the first light source 1a and that of the second light source 1b.

20

25

FIG. 10B shows an example of a beam pattern on the light-receiving elements of the photodetector 16.

00616364.071300

For example, the beam pattern is for a CD. In the beam pattern, the main beam is divided in two and each sub-beam is also divided in two. The operating principle is similar to that of the diffraction grating explained earlier.

FIG. 11A is a side view of an optical head device having the hologram 13 placed as shown in FIG. 10A. In such an arrangement, the using area of the light beam 8a from the first light source 1a and that of the light beam 8b from the light source 1b are placed in such a manner that they are shifted from the center of the hologram pattern 3a in the opposite direction to each other. In FIG. 11D, the abscissa axis indicates the light beam position on the hologram and the ordinate axis indicates the focus error signal amplitude.

As seen from the relationship between the focus error amplitude and the light beam position on the hologram pattern of FIG. 11D, the arrangement of FIG. 11A provides a larger focus error amplitude even in that state. Namely, a larger amplitude of the focus error signal can be obtained in both DVD playback and CD playback. As seen from FIG. 11D, the location of the hologram in FIG. 9A produces only a smaller focus error signal in DVD playback.

With the above configuration, the amplitude of a suitable focus error signal can be obtained in both DVD playback and CD playback, improving the reliability

09615354.071300

of the pickup device.

On the other hand, the photodiodes 6a to 6d (FIG. 10B) of the photodetector 16 receive the light beams quadrisedected by the hologram pattern 3a and detect the phase difference between the respective amounts of light received, thereby obtaining a DVD tracking error signal. Therefore, it is desirable that the light beam 8a in DVD playback should be closer to the center of the hologram pattern 3a. In contrast, the tracking error signal in CD playback is independent of the relative position between the hologram pattern 3a and the light beam 8b, because a three-beam method is used. Taking into account the tracking error signal, the CD mode has a more margin for the positional gap between the hologram pattern 3a and the light beam than the DVD mode.

Therefore, the amplitude of the tracking error signal can be obtained suitably by placing the center of the hologram 13 closer to the first light source 1a than the midpoint between the first light source 1a and second light source 1b with respect to the optical axis of the optical system.

The focus error signal is sensed in the lens action by a mixed aberration method (refer to U.S. Pat. No. 5,161,139).

The above device of the present invention comprises a first light source, a second light

00616364.071300

embodiments. Hereinafter, still another embodiment of the present invention will be explained.

Since in an optical pickup using a multi-wavelength semiconductor array, the DVD light source is separated from the CD light source, the position on the hologram at which the light source is projected in the direction of optical axis disagrees with the center of the hologram. This causes the problem of degrading the quality of the focus error signal. To overcome this problem, it is desirable that the hologram should be placed as far away from the semiconductor laser array as possible.

On the other hand, because the hologram is used in both DVD and CD, it is desirable that the level of the playback signal should not vary due to the birefringence of the disk. To achieve this, use of a nonpolarization hologram can be considered. When a nonpolarization hologram is used, the 0-order light from the hologram is projected via the objective lens onto the disk in the transmit light system and the + first-order light from the hologram is directed to the photodetector in the reflection system. The - first-order light in the transmit light system arrives at the photodetector as the 0-order light in the reflection system, causing stray light. The stray light contributes to the deterioration of the quality of the playback signal. To reduce such stray light, it

is desirable that the hologram should be placed close to the semiconductor laser array and the diffraction angle be made larger to cause an aperture to cut off the first-order light in the transmit light system.

5 As described above, to achieve a good-quality focus error signal, the distance between the semiconductor laser array and the hologram should be as large as possible. To reduce stray light, the distance between the semiconductor laser array and the hologram
10 should be as close as possible. These two requirements disagree with each other.

 To overcome this problem, the present invention makes it possible to set the optimum distance between the semiconductor laser array and the hologram.

15 FIG. 12A shows the configuration of an optical head device. In DVD playback, the light emitted from the first light source 1a enters the hologram 13. The light emitted from the hologram 13 is converted by the collimator lens 14 into collimated light.
20 The collimated light emitted from the collimator lens 14 is limited by an aperture to a suitable numerical aperture. The resulting light enters the objective lens 15. The objective lens 15 projects the light in such a manner that the light converges
25 on the recording surface of the recording medium. The reflected light from the recording medium passes through the objective lens 15, aperture, and collimator

00616364.071300

lens 14 and enters the hologram 13. The hologram 13 emits the + first-order light, which is then directed to the photodetector 16. The photodetector 16 converts the light into an electronic signal.

5 In CD playback, the second light source 1b is used. The light emitted from the light source 1b passes through the same route as described above. The reflected light from the recording medium is directed to the photodetector 16.

10 As described above, with the optical head device, the single hologram 13 is shared by the first light source and second light source. Since the diffraction angle at the hologram 13 is almost proportional to the wavelength, the first light source 1a for DVD of
15 a shorter wavelength is placed on the photodetector 16 side and the second light source 1b for CD is placed farther away from the photodetector 16 than the first light source 1a. This arrangement enables the single photodetector 16 to receive the light from both the
20 first and second light sources.

 Since the diffraction angle is almost proportional to the wavelength, the distance from the first light source 1a to the second light source 1b is also proportional to the distance from the first light
25 source 1a to the photodetector 16.

 As shown in FIG. 12A, in a multi-wavelength semiconductor laser, because the first light source

00316364-071300

is separated from the second light source, it is impossible to cause the positions at which the first light source and second light source are projected on the hologram in the direction of optical axis to coincide with the center of the hologram 13 at the same time. Consequently, the beam deviates from the center of the hologram pattern of the hologram 13 as shown in FIG. 12B.

In FIG. 12C, the abscissa axis indicates the ratio of the distance from the semiconductor laser light source to the hologram 13 to the distance between the two light sources, and the ordinate axis indicates the amplitude of the focus error signal. As the distance from the semiconductor laser light source to the hologram 13 becomes larger, the beam on the hologram 13 becomes larger, which makes the effect of a shift in the light source relatively small and increases the amplitude of the focus error signal.

If the amplitude of the focus error signal with no shift in the light source is 1, the allowed value of a drop in the amplitude is 0.8. Thus, it is desirable that the ratio of the distance from the semiconductor laser light source to the hologram 13 to the distance between the two light sources should be 20 or more.

On the other hand, as shown in FIG. 12A, part of the - first-order light from the hologram in the transmit light system might not be limited by the

5 In FIG. 12D, the abscissa axis indicates the
ratio of the amount of the 0-order light to the
amount of the - first-order light in the transmit light
system, and the ordinate axis indicates playback signal
jitters. As the amount-of-light ratio is higher,
0 the signal-to-noise ratio is improved more, reducing
playback signal jitters.

It will be understood from what has been described above that an optical head which produces a good-quality focus error signal and provides a good playback performance of playback signals by setting the ratio of the distance from the semiconductor laser light source to the hologram 13 to the distance between the two

5 FIG. 13C shows an example of a state where the second light source 1b is fitted on the marker 3a provided at the center of the hologram pattern of the hologram 13 and the optical axis directed to the photodetector 16 is fitted on the marker 3b.

15 FIGS. 13D and 13E show examples of the beam spots
formed on the quadrisected diodes of the photodetector
16, when the position is aligned in such a state.

Although FIG. 13D shows the beam spot of the main beam for DVD, the spot of the reflected light directed onto the photoelectric conversion element of the photodetector 16 deviates slightly from the desired position on the photoelectric conversion element, because the projected spot of the first light source 1a on the hologram deviates from the line connecting the markers 3a and 3b. Namely, the spot of the reflected light is asymmetrical on the dividing line. In the case of a DVD beam, however, because the aperture is

large, the diameter of the beam spot is so large that the deviation of the spot from the desired position has almost no adverse effect on the playback function of the playback signal. Specifically, the effect of the deviation on the playback performance is less than the effect of a shift in the CD beam spot on the playback performance.

In contrast, FIG. 13E shows beam spots of the CD main beam. As shown in FIG. 13C, because the second light source 1b is so adjusted that the projected spot on the hologram coincides with the marker 3a, the spot of the reflected light directed to the photodetector 16 coincides with the desired position on the photoelectric conversion element.

The present invention is not limited to the above embodiments and may be applied to a method as shown in FIGS. 14A - 14C. Specifically, a first marker 3a is provided halfway between the projected positions of the first and second light sources 1a and 1b of the semiconductor laser device 11 and a marker 3b is provided at the position at which the midpoint of the quadrisected diodes of the photodetector 16 is projected in the direction of optical axis. The semiconductor laser device 11 and photodetector 16 are provided on a substrate (not shown). When the hologram 13 is mounted on the substrate, the semiconductor laser device 11 and photodetector 16 are viewed along the

optical axis and the hologram is adjusted in such a manner that the marker 3a on the hologram 13 coincides with the center of the light source 1a and that of the light source 1b and the second marker 3a on the hologram 13 coincides with the center of the main beam detector (the center of the quadrisectioned diodes) of the photodetector 16. Then, the hologram is secured to the substrate. With this configuration, even when the semiconductor laser device 11 is provided a little away from the desired position (for example, rotated a little as shown in FIG. 14A), both the first light source 1a for DVD and the second light source 1b for CD are placed in such a manner that they deviate from the markers on the hologram 13. As a result, both the DVD beam spot and CD beam spot on the photodetector 16 are formed asymmetrically with the dividing line as shown in FIGS. 14B and 14C. In this embodiment, the playback performance will not deteriorate seriously in only either DVD playback or CD playback.

In the optical head device, if the numerical aperture when the light beam from the first light source is used is $NA1$ and the numerical aperture when the light beam from the second light source is used is $NA2$, the following expression $NA1 > NA2$ is satisfied.

In the concept of the present invention, the technical ideas explained in FIGS. 1, 7A, 7B, 7C, and 7D may be combined for application. In addition, the

technical idea explained in FIGS. 8A - 8C may be selectively applied to or be combined with the technical ideas in FIGS. 1 and 7A.

5 The present invention includes both of the technical idea explained in FIG. 8A and that explained in FIG. 10A. A combination of the technical ideas in FIGS. 8A and 10A and that explained in FIG. 7A is also within the scope of the invention.

10 The technical idea explained in FIG. 12A may be combined with each of the above technical ideas.

As explained above, with the present invention, side beams are allowed to occur when a light source of a first wavelength is used, whereas side beams are prevented from occurring when a light source of
15 a second wavelength is used. This improves the light use efficiency of the second light source.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to
20 the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

09616364, 071300